



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 25/01	A1	(11) International Publication Number: WO 99/25413 (43) International Publication Date: 27 May 1999 (27.05.99)
<p>(21) International Application Number: PCT/US98/24758</p> <p>(22) International Filing Date: 18 November 1998 (18.11.98)</p> <p>(30) Priority Data: 08/972,654 18 November 1997 (18.11.97) US</p> <p>(71) Applicant: ADVANCED CARDIOVASCULAR SYSTEMS, INC. [US/US]; 3200 Lakeside Drive, P.O. Box 58167, Santa Clara, CA 95052-8167 (US).</p> <p>(72) Inventor: McMAHON, James, C.; 30357 San Pasqual Road, Temecula, CA 92591 (US).</p> <p>(74) Agents: LYNCH, Edward, J.; Heller, Ehrmann, White & McAuliffe, 525 University Avenue, Palo Alto, CA 94301-1900 (US) et al.</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: GUIDEWIRE WITH SHAPED INTERMEDIATE PORTION</p> <div data-bbox="310 1115 1299 1344"> </div> <p>(57) Abstract</p> <p>A guidewire (10) for advancing a medical device such as a catheter through a patient's body lumen which has an elongated core (11) with proximal (12) and distal core (13) sections, a flexible tubular member such as a coil (14) on the distal end and an intermediate portion, preferably formed at least in part by a polymeric sheath (15) proximal to the coil having contact regions (17) and recessed non-contact regions (18).</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

GUIDEWIRE WITH SHAPED INTERMEDIATE PORTION**BACKGROUND OF THE INVENTION**

This invention relates to the field of guidewires for advancing intravascular devices such as stent delivery catheters, balloon dilatation catheters and
5 atherectomy catheters within a body lumen

Conventional guidewires for angioplasty, stent delivery, atherectomy and other vascular procedures usually comprise an elongated core member with one or more tapered sections near the distal end thereof and a flexible body such as a helical coil or a tubular body of polymeric material disposed about the distal
10 portion of the core member. A shapable member, which may be the distal extremity of the core member or a separate shaping ribbon which is secured to the distal extremity of the core member extends through the flexible body and is secured to the distal end of the flexible body by soldering, brazing or welding which forms a rounded distal tip. Torquing means are provided on the proximal
15 end of the core member to rotate, and thereby steer, the guidewire while it is being advanced through a patient's vascular system.

Further details of guidewires, and devices associated therewith for various interventional procedures can be found in U.S. Patent 4,748,986 (Morrison et al.); U.S. Patent 4,538,622 (Samson et al.); U.S. Patent 5,135,503 (Abrams);
20 U.S. Patent 5,341,818 (Abrams et al.); and U.S. Patent 5,345,945 (Hodgson, et al.) which are hereby incorporated herein in their entirety by reference thereto.

In a typical coronary procedure using a guidewire, a guiding catheter having a preformed distal tip is percutaneously introduced into a patient's peripheral artery, e.g. femoral or brachial artery, by means of a conventional
25 Seldinger technique and advanced and steered therein until the distal tip of the guiding catheter is seated in the ostium of a desired coronary artery.

There are two basic techniques for advancing a guidewire into the desired location within the patient's coronary anatomy through the in place guiding catheter. The first is a preload technique which is used primarily for over-the-
30 wire (OTW) devices and the second is the bare wire technique which is used primarily for rail type systems.

With the preload technique, a guidewire is positioned within an inner lumen of an OTW device such as a dilatation catheter or stent delivery catheter with the distal tip of the guidewire just proximal to the distal tip of the catheter and then both are advanced through the guiding catheter to the distal end thereof. The guidewire is first advanced out of the distal end of the guiding catheter into the patient's coronary vasculature until the distal end of the guidewire crosses the arterial location where the interventional procedure is to be performed, e.g. a lesion to be dilated or a dilated region where a stent is to be deployed. The catheter, which is slidably mounted onto the guidewire, is advanced out of the guiding catheter into the patient's coronary anatomy over the previously introduced guidewire until the operative portion of the intravascular device, e.g. the balloon of a dilatation or a stent delivery catheter, is properly positioned across the arterial location. Once the catheter is in position with the operative means located within the desired arterial location, the interventional procedure is performed. The catheter can then be removed from the patient over the guidewire. Usually, the guidewire is left in place for a period of time after the procedure is completed to ensure reaccess to the arterial location is it is necessary. For example, in the event of arterial blockage due to dissected lining collapse, a rapid exchange type perfusion balloon catheter such as described and claimed in U.S. Patent 5, 516,336 (McInnes et al), can be advanced over the in-place guidewire so that the balloon can be inflated to open up the arterial passageway and allow blood to perfuse through the distal section of the catheter to a distal location until the dissection is reattached to the arterial wall by natural healing.

With the bare wire technique, the guidewire is first advanced by itself through the guiding catheter until the distal tip of the guidewire extends beyond the arterial location where the procedure is to be performed. Then a rail type catheter, such as described in U.S. Patent No. 5,061,395 (Yock) and the previously discussed McInnes et al. which are incorporated herein by reference, is mounted onto the proximal portion of the guidewire which extends out of the proximal end of the guiding catheter which is outside of the patient. The catheter is advanced over the catheter, while the position of the guidewire is

fixed, until the operative means on the rail type catheter is disposed within the arterial location where the procedure is to be performed. After the procedure the intravascular device may be withdrawn from the patient over the guidewire or the guidewire advanced further within the coronary anatomy for an additional
5 procedure.

SUMMARY OF THE INVENTION

The present invention is directed to an improved guidewire having a flexible distal section which facilitates advancement through a patient's body
10 lumen.

The guidewire of the present invention has an elongated core member with proximal and distal core sections with a flexible tubular member such as a helical coil is disposed about and secured to the distal part of the distal core section. The distal core section has one or more distally tapering segments.
15 Proximal to the flexible tubular member, the guidewire has an exterior surface which is shaped to provide a plurality of contact regions and non-contact regions between adjacent contact regions.

In one presently preferred embodiment, the intermediate portion is defined by a sheath disposed about the core member and preferably formed of a
20 polymeric material. The contact region or regions of the intermediate portion of the guidewire is generally about 20 to about 60% of the surface of the sheath. The outer diameter of the contact regions of the intermediate portion is preferably the same or approximately the same as the outer diameter of the flexible tubular member or coil on the distal part of the distal shaft section.
25 However, if the flexible tubular member is of different outer diameter than the proximal core section, the intermediate portion may taper from the outer diameter of the proximal core section to the outer diameter of the coil. The distances between the peaks of the contact regions should be about 0.05 to about 5.0 mm, preferably about 0.1 to about 0.5 mm. The depth of the
30 recessed non-contact regions may be about 0.01 to about 0.1 mm, preferably about 0.025 to about 0.075 mm as measured from the peaks of the contact regions. While the presently preferred intermediate portion of the guidewire

having the contact and non-contact regions extends distally from the flexible tubular member and terminates distal to the proximal core section, the section having the contact and non-contact regions can extend proximally over most or all of the proximal core section.

5 By reducing the area of surface contact between the guidewire and a body lumen or a catheter lumen in which the guidewire is being moved relative thereto, the resistance to movement is greatly reduced. In one embodiment of the invention, solid or liquid lubricant can be maintained within recessed non-contact regions to further reduce frictional drag on the guidewire as it moves
10 through a lumen or the frictional drag on a catheter as the catheter is moved over the intermediate portion of the guidewire. Pharmaceutical materials and diagnostic and therapeutic agents may also be incorporated into the recessed non-contact regions.

In one presently preferred embodiment of the invention, the intermediate
15 guidewire portion having the contact and non-contact regions is defined by an intermediate sheath disposed about at least part of the distal guidewire section proximal to the flexible tubular member or coil on the distal part of the distal section.

These and other advantages of the invention will become more apparent
20 from the following detailed description of the invention when taken in conjunction with the accompanying exemplary drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an elevational view partially in section of a guidewire embodying
25 features of the invention wherein a sheath forming the intermediate portion has a helically shaped ridge.

Fig. 2 is a transverse cross-sectional view of the guidewire shown in Fig.
1 taken along the lines 2-2.

Fig. 3 is a transverse cross-sectional view of the guidewire shown in Fig.
30 1 taken along the lines 3-3.

Fig. 4 is an elevational view partially in section of an alternative embodiment of the invention wherein a sheath on the intermediate portion has an undulating exterior surface.

Fig. 5 is a transverse cross-sectional view of the embodiment shown in Fig. 4
5 taken along the lines 5-5.

Fig. 6 is an elevational view partially in section of an alternative embodiment of the invention wherein the intermediate section has a closed figure design formed into the exterior surface thereof.

Fig. 7 is a transverse cross-sectional view of the embodiment shown in Fig. 6
10 taken along the lines 7-7.

DETAILED DESCRIPTION OF THE INVENTION

Figs 1-3 depict a guidewire 10 embodying features of the invention which has an elongated core member 11 with a proximal core section 12, a distal core
15 section 13 and a helical coil 14 on the distal extremity of the distal core section.

An intermediate portion of the guidewire 10 proximal to the helical coil 14 is provided with a sheath 15, which is disposed about and secured to the distal core section 13, has an exterior surface 16 with contact regions 17 in the form of a helical ridge and a plurality of recessed (with respect to the contact regions)
20 non-contact regions 18 disposed between adjacent contact regions. The peak-to-peak distance between the adjacent contact regions 17 is about 0.05 to about 5 mm, preferably about 0.1 to about 0.5 mm.

The distal end of coil 14 is secured to the distal tip of the distal core section 13 by suitable means, such as solder, a weldment, an adhesive, a body
25 of polymeric material and the like which forms the rounded tip 20. The proximal end of the coil 14 is secured to the distal core section by solder 21. The proximal core section 12 has a polymeric jacket 22 which is preferably formed of lubricious polymeric materials such as fluoropolymers or hydrophilic materials. Other lubricious materials may be utilized.

30 An alternative embodiment of the invention is depicted in Figs. 4 and 5 wherein the guidewire 30 has an intermediate portion proximal to the helical coil 31 covered with a sheath 32 which has an undulating exterior surface 33 with

contact regions 34 in the form of a plurality of circular ridges and a plurality of recessed non-contact regions 35 between adjacent contact regions. The peak-to-peak distances between the contact surfaces 34 of this embodiment are the same or approximately the same as that for the contact regions 17 of the
5 previously described embodiment.

Figs. 6 and 7 illustrate yet another alternative embodiment of the invention in which the guidewire 40 has an intermediate portion with a sheath 41 with a closed figure texture formed in the exterior surface 42 with contact regions 43 and recessed non-contact regions 44 for essentially the same
10 purpose as the contact and non-contact regions of the previously discussed embodiments. The recessed non-contact regions may contain liquid or solid lubricant such as a fluoropolymer, a silicone coating such as MICROGLIDE™, or HYDROCOAT™. These recesses may also be employed as reservoirs for pharmaceutical materials, therapeutic agents or diagnostic agents.

15 The sheaths forming the intermediate portions of the guidewires of the present invention may be formed by first heat shrinking a thermoplastic polymeric material onto the distal core section proximal to the coil and then placing a clam-shell mold of the desired configuration about the heat shrunk material at elevated temperatures to shape the exterior of the intermediate
20 sheath in the desired configuration. Other means may also be employed. For example, the exterior surface of a tubular polymeric member may first be formed into the desired shape and then the tubular member heat shrunk onto the distal core section. Other means including casting polymeric material about the distal core section into the desired shape. Machining polymeric material from the
25 exterior of a tubular polymeric member on the distal core segment may also be employed to develop the contact and non-contact regions of the intermediate sheath. Suitable polymeric materials for the intermediate sheath include polyethylene, polyetheretherketone, polyvinyl chloride and polyurethane. A wide variety of other polymeric materials are contemplated. The sheathed
30 intermediate portion of the guidewire is about 4 to about 38 cm in length, preferably about 6 to about 20 cm in length.

The guidewires of the invention may have typical guidewire dimensions.

Guidewire length may generally be about 90 to about 300 cm, and for use within a patient's coronary anatomy commercially available guidewires are typically about 175 cm in length. Recently, however, longer guidewires, e.g. up to 190 cm in length, are being offered commercially by a variety of suppliers, including the present assignee. The proximal core section 12 may have a length of about 65 to about 280 cm, preferably about 150 to about 200 cm and a diameter generally about 0.008 to about 0.035 inch (0.20-0.89 mm), typically about 0.010 to about 0.020 inch (0.25-0.51 mm) for coronary artery uses. The distal core section is preferably much shorter than the proximal core section and generally is about 6 to about 40 cm, preferably about 8 to about 30 cm in length and tapers in the distal direction in one or more steps to smaller transverse dimensions.

The core member is preferably coated with a lubricous coating such as a fluoropolymer, e.g. TEFLON[®] available from DuPont, which extends the length of the proximal core section 12. The distal section 13 is also provided a lubricous coating, not shown for purposes of clarity, such as a MICROGLIDE[™] coating used by the present assignee, Advanced Cardiovascular Systems, Inc. on many of its commercially available guidewires.

The tapered portion of the distal core segment is preferably followed distally with a manually shapable flattened core segment or shaping ribbon of about 1 to 4 cm in length which preferably has essentially constant transverse dimensions, e.g. 0.0005-0.002 inch (0.013-0.051 mm) by 0.002-0.006 inch (0.051-0.152 mm), typically about 0.001 by 0.003 inch (0.025-0.076 mm). A helical coil having transverse outer dimensions about the same as or slightly less than the proximal core section is secured by its distal end to the flattened distal tip of the core member, e.g. by means of solder, and by its proximal end at an intermediate position on the tapered distal core segment so that the distal end of the tapered core segment resides within the interior of the coil. The helical coil 14 may be formed all or in part of stainless steel, a suitable radiopaque material such as platinum or alloys thereof or other material such as stainless steel coated with a radiopaque material such as gold. The wire from which the coil is

made generally has a transverse diameter of about 0.0015 to about 0.003 inch (0.04-0.08 mm) for coronary applications and up to 0.07 inch (0.18 mm) for peripheral applications. The overall length of the coil 14 is about 2 to about 15 cm, preferably about 2 about 6 cm. Multiple turns of the coil 14 may be
5 expanded to provide additional flexibility.

Unless otherwise described herein, conventional materials and manufacturing methods may be used to make the guiding members of the present invention. Additionally, various modifications may be made to the present invention without departing from the scope thereof. Although individual
10 features of embodiments of the invention may be shown in some of the drawings and not in others, those skilled in the art will recognize that individual features of one embodiment of the invention can be combined with any or all the features of another embodiment.

WHAT IS CLAIMED IS:

1. A guidewire for intraluminal advancement of a medical device within a patient, comprising:
 - a) an elongated core member which has a proximal core section
5 and a distal core section;
 - b) a flexible body which is disposed about and secured to a portion of the distal core section; and
 - c) an intermediate portion which is disposed at a location proximal to the flexible body and which has an exterior with a plurality of contact
10 regions and recessed non-contact regions disposed between contact regions.
2. The guidewire of claim 1 wherein the contact regions form a helical ridge on the intermediate portion which encircles the core member at least one time.
3. The guidewire of claim 1 wherein the contact regions form a plurality of circular ridges on the intermediate portion which are disposed about the core
15 member.
4. The guidewire of claim 1 wherein the intermediate portion has a closed figure texture formed in the exterior with the contact regions surrounding non-contact regions.
5. The guidewire of claim 1 wherein recessed non-contact regions are
20 configured to hold a component selected from the group consisting of a lubricant, a therapeutic agent and a diagnostic agent .
6. The guidewire of claim 1 wherein the intermediate portion having contact and non-contact regions is defined by a sheath.
7. The guidewire of claim 6 wherein the sheath is formed of a polymeric
25 material.
8. The guidewire of claim 7 wherein the polymeric material is a heat shrunk thermoplastic.
9. The guidewire of claim 6 wherein the contact regions comprise about 20 to about 60% of the surface of the intermediate sheath.
- 30 10. The guidewire of claim 1 wherein the contact regions are spaced about 0.05 to about 5 mm.

11. The guidewire of claim 1 wherein the contact regions are spaced about 0.1 to about 0.5 mm.

12. The guidewire of claim 1 wherein the recessed non-contact regions have depths of about 0.01 to about 0.1 mm.

5 13. The guidewire of claim 1 wherein the recessed non-contact regions have depths of about 0.025 to about 0.075 mm.

14. The guidewire of claim 1 wherein the intermediate sheath has a proximal portion with an outer diameter approximately the same as the outer diameter of the proximal core section.

10 15. The guidewire of claim 1 wherein the intermediate sheath has a distal portion with an outer diameter approximately the same as the outer diameter of the flexible tubular member.

16. The guidewire of claim 1 wherein the intermediate sheath is about 4 to about 38 cm in length.

15 17. The guidewire of claim 1 wherein the intermediate sheath is about 6 to about 20 cm in length.




FIG. 1

1/2




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

national Application No
PCT/US 98/24758

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61M25/01

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 377 453 A (BAKER SUSAN) 11 July 1990 see column 3, line 6 - column 4, line 9 see column 4, line 44-47 see column 5, line 12-14; figures 1-3 ---	1-3
X A	US 5 497 785 A (VIERA FERNANDO M) 12 March 1996 see column 2, line 38 - column 3, line 8 see column 4, line 12-64 see column 5, line 6-10 see column 5, line 30-65 see column 6, line 7-16 see figure 3 ---	1-3, 10-12 17
A	WO 89 10088 A (TARGET THERAPEUTICS INC) 2 November 1989 see page 8, line 19 - page 13, line 3 see figures 1,6 --- -/--	1,5-7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

23 February 1999

Date of mailing of the international search report

04/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Bichlmayer, K-P

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 98/24758

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 606 979 A (HODGSON WILLIAM S) 4 March 1997 see column 3, line 23-26 ---	8
A	WO 92 14508 A (MALLINCKRODT MEDICAL INC) 3 September 1992 see abstract ---	5
A	US 5 095 915 A (ENGELSON ERIK T) 17 March 1992 see column 1, line 63 - column 2, line 23 see figures 2,4,7 ---	1
A	US 5 345 945 A (HODGSON WILLIAM S ET AL) 13 September 1994 cited in the application see column 2, line 63 - column 3, line 51 see figure 1A -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 98/24758

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0377453	A	11-07-1990	DE 8900077 U	17-05-1990
US 5497785	A	12-03-1996	NONE	
WO 8910088	A	02-11-1989	US 4884579 A	05-12-1989
			AT 110972 T	15-09-1994
			AU 624383 B	11-06-1992
			AU 3554389 A	24-11-1989
			CA 1307987 A	29-09-1992
			DE 8916214 U	16-02-1995
			DE 68918092 D	13-10-1994
			DE 68918092 T	12-01-1995
			EP 0411040 A	06-02-1991
			JP 3505168 T	14-11-1991
US 5606979	A	04-03-1997	EP 0700271 A	13-03-1996
			JP 8510675 T	12-11-1996
			WO 9427654 A	08-12-1994
WO 9214508	A	03-09-1992	AU 1428792 A	15-09-1992
US 5095915	A	17-03-1992	AU 651094 B	14-07-1994
			AU 7561891 A	21-10-1991
			CA 2077558 A	20-09-1991
			EP 0521091 A	07-01-1993
			WO 9114395 A	03-10-1991
			US 5599492 A	04-02-1997
US 5345945	A	13-09-1994	CA 2090605 A	01-03-1992
			DE 69129539 D	09-07-1998
			EP 0546094 A	16-06-1993
			JP 6501179 T	10-02-1994
			WO 9204072 A	19-03-1992